



For performance that's **OFF THE CHART** of ordinary pumps!

# Specifications

## Artesian2 Low RPM

MODEL	HP	TYPE	RPM	VOLTAGE	HZ.	MAX WATTS	WATTS @ MAX HEAD**	WATTS @ MAX FLOW**	LIST PRICE
A2-1/8-39	1/8	1Ø TEFC	1725	115/230	50/60	202	112 @ 17 ft.	165 @ 3900 GPH @ 3'	\$679.00
A2-1/4-47	1/4	1Ø TEFC	1725	115/230	50/60	290	170 @ 22 ft.	250 @ 4680 GPH @ 4'	\$710.00
A2-1/4-58	1/4	1Ø TEFC	1725	115/230	50/60	360	180 @ 23 ft.	320 @ 5760 GPH @ 5'	\$729.00
A2-1/3-63	1/3	1Ø TEFC	1725	115/230	50/60	450	200 @ 26 ft.	440 @ 6300 GPH @ 6'	\$767.00
A2-1/2-76	1/2	1Ø TEFC	1725	115/230	50/60	630	260 @ 26 ft.	630 @ 7560 GPH @ 8'	\$817.00

## Artesian2 High Flow

MODEL	HP	TYPE	RPM	VOLTAGE	HZ.	MAX WATTS/AMPS	AMPS @ 230V @ MAX HEAD**	AMPS @ 230V @ MAX FLOW**	LIST PRICE
A2-1/2-HF	1/2	1Ø ODP	3450	115/230	60	930 / 4.2	2.2 @ 45 ft.	3.5 @ 7380 GPH @ 8'	\$649.00
A2-3/4-HF	3/4	1Ø ODP	3450	115/208-230	60	1270 / 5.6	2.7 @ 55 ft.	4.8 @ 8880 GPH @ 11'	\$706.00
A2-1-HF	1	1Ø ODP	3450	115/208-230	60	1640 / 7.3	3.5 @ 65 ft.	6.4 @ 9840 GPH @ 13'	\$760.00
A2-11/2-HF1	1 1/2	1Ø ODP	3450	115/208-230	60	1940 / 9.0	5.9 @ 54 ft.	8.4 @ 11,400 GPH @ 17'	\$823.00
A2-2-HF	2	1Ø ODP	3450	208-230	60	2300 / 10.0	5.5 @ 55 ft.	9.8 @ 12,840 GPH @ 20'	\$911.00
A2-3-HF	3	1Ø ODP	3450	208-230	60	3100 / 13.6	7.7 @ 64 ft.	13.6 @ 14,040 GPH @ 24'	\$999.00

## Artesian2 High Head

MODEL	HP	TYPE	RPM	VOLTAGE	HZ.	MAX WATTS/AMPS	AMPS @ 230V @ MAX HEAD**	AMPS @ 230V @ MAX FLOW**	LIST PRICE
A2-1/2-HH	1/2	1Ø ODP	3450	115/230	60	940 / 4.2	2.4 @ 54 ft.	3.3 @ 6660 GPH @ 7'	\$649.00
A2-3/4-HH	3/4	1Ø ODP	3450	115/208-230	60	1250 / 5.6	3.2 @ 70 ft.	4.2 @ 7140 GPH @ 8'	\$706.00
A2-1-HH	1	1Ø ODP	3450	115/208-230	60	1680 / 7.4	4.1 @ 78 ft.	5.8 @ 8580 GPH @ 10'	\$760.00
A2-11/2-HH1	1 1/2	1Ø ODP	3450	115/208-230	60	1970 / 9.1	5.5 @ 83 ft.	7.5 @ 9600 GPH @ 13'	\$823.00
A2-2-HH	2	1Ø ODP	3450	208-230	60	2200 / 9.9	5.0 @ 86 ft.	8.4 @ 11,040 GPH @ 16'	\$911.00
A2-3-HH	3	1Ø ODP	3450	208-230	60	2900 / 13.1	7.1 @ 93 ft.	12.2 @ 12,000 GPH @ 18'	\$999.00

## Features & Options

- \* Designed to operate at any point on specified performance curve.
- \* Minimum recommended continuous flow rate of five gallons per minute.
- \* 2" female NPT suction and discharge ports.
- \* All 1725 RPM motors are enclosed for extra protection and long life.

- \* 316 stainless steel shaft seal.
- \* A 16 AWG, 8 ft. cord with 115 volt plug is optional (1725 rpm, 1/2HP max).
- \* A 12 AWG, 8 ft. cord with 115 volt plug is optional (3450 rpm, 1hp max).
- \* Saltwater kits available for an additional \$91.00.

- \* A \$5.50 handling & packaging fee applies to each unit.
- \* 3 year limited warranty for fresh water applications.
- \* 1 year limited warranty for salt water applications.

\*\* Watt and Amp draw ratings are typical but may vary with alternate motors and operating voltages.

## PerformancePro Pumps Inc.

5976 S.E. Alexander St., Suite F, Hillsboro, Oregon 97123  
 Phone: 503/356-5888 Fax: 503/356-1660  
 www.performancepropumps.com