



For performance that's **OFF THE CHART** of ordinary pumps!

SPECIFICATIONS

WellSpring

MODEL	HP	TYPE	FLA	VOLTAGE	HZ.	WATTS @ MAX. HEAD*	WATTS @ MAX. FLOW*	MAX WATTS*
WS1/4-33	1/4	1Ø	3.1	120	60	319 @ 20 ft.	410 @ 3100 GPH @ 1'	410
WS1/3-44	1/3	1Ø	4.2	120	60	388 @ 27 ft.	546 @ 4100 GPH @ 3'	546
WS1/2-58	1/2	1Ø	6.0	120	60	435 @ 38 ft.	728 @ 5100 GPH @ 4'	728
WS1-66	1	1Ø	9.9	120	60	542 @ 46 ft.	922 @ 6000 GPH @ 5'	922

* Ratings are the maximum true watts measured at 120 volts plus or minus .6 volts.

Features & Options

- Designed to operate at any point on specified performance curve.
- Minimum recommended continuous flow rate of one gallon per minute.
- 16 AWG, 18 ft. cord with 115 volt plug included.
- 2 year limited warranty (for fresh water applications only).

Pump Specifications		
MODEL	PORT SIZE	ADAPTER (Included)
WS1/4-33	2" Female Thread	2" Barbed
WS1/3-44	2" Female Thread	2" Barbed
WS1/2-58	2" Female Thread	2" Barbed
WS1-66	2" Female Thread	2" Barbed

PerformancePro Pumps Inc.

Effective Date: January 1, 2019

5976 S.E. Alexander St., Suite F, Hillsboro, Oregon 97123
 Phone: 503/356-5888 Fax: 503/356-1660
 www.performancepropumps.com